

Description

100% Synthetic Oil with Antifriction Additive

WS 1330 S/15 Works is a 100% synthetic high-viscosity oil with exclusive WS Works additive. Although it is primarily formulated for chain lubrication, its versatility means it can also be used on guides, hinges, worm gears, and cables with complete effectiveness. It offers excellent results in terms of chain life (up to 5 times longer). It guarantees a low friction coefficient, lower energy consumption, less wear, high water resistance, and stability at high temperatures.

Features

- Withstands temperatures from -38° to 280°C.
- Excellent wear protection.
- Extreme properties under high loads.
- Low evaporation at high temperatures.
- High oxidation stability.
- Good sliding characteristics, penetrates between chain spaces.
- Exceptional lubrication and separating effect.
- Reduces the coefficient of friction to a minimum.
- Protects against corrosion.
- High viscosity index, stable to temperature changes.
- Antistatic film that repels dust.

Applications

- Industrial chains of all types, for example: in pasteurization plants, drying ovens, lacquering ovens, the textile industry, and other assembly lines and packaging equipment.
- Forklift chains.
- Conveyor chains.
- Motorcycle chains.
- Go-kart chains.
- Guides, augers, cables, hinges, etc.

How to use

- Shake well before use. It is recommended to clean the parts thoroughly before using the product.
- Apply a thin layer to the parts to be lubricated; do not apply excessively.

Technical Data (Without Propellant)

Features	Unit	Typical Value	Norm
Referencia	----	WS 1330 S/15 Works	----
Appearance	----	Liquid	----
Colour	----	Light brown	----
Odor	----	Characteristic	----
Kinematic viscosity at 40°C	cSt	460	ASTM D-445
Viscosity index	ISO	125	DIN 2909
Flash point	°C	-36	----
Freezing point	°C	-38	----
Operating temperature	°C	-38 a 280	----
Product shelf life	years	5	----